

DRYERS: Electric Dryer

MED10ZEMW







Moisture Sensor

Specifications:

•	
Drum Capacity (Liter)	198 Liters
Drum Material	Steel Painted White
Tumbling Speed (rpm)	50 Rotations Per Minute
Sound Insulation	No
Heating Element (watts)	4300 Watts
Air Flow (CFM)	200 Cubic Feet Per Minute
Door Material	Solid Metal
Moisture Sensor	No
Shrink Guard	No
Color	WHITE
Hertz	50/60
Volts	220-240
Unit Dimensions (cm)	68.58w x 111.76h x 73.66d
Unit Weight (kg)	59.42
Carton Dimensions (cm)	73.66w x 116.84h x 81.28d
Carton Weight (kg)	64.86

Features:



Extra Large Capacity

Saves time by drying more in one load with its large 7.0 cu.ft interior

Balanced Dry System

Forces large amounts of air through the back of the dryer drum. This system of air distribution results in an evenly dried load of laundry.

Drying Programs: 8

Auto drying programs save time and energy while protecting your fabrics.

Timer Program (minutes):

15 / 30 / 60 / 90

End-of-Cycle Signal

To help you be more efficient and organized the End-of-Cycle Signal alerts you that the drying cycle is complete.

Drying Progress Indicator:

LE

The Drying Progress Indicators show the exact stage of the drying cycle.

Refresh Cycle (no heat)

Helps remove wrinkles from clothing that was previously washed.

$\textbf{Temperature Options:}\ 4$

Vented

Control Type: Rotary Electronic

Control Panel Language:

English

Reversible Door

The Reversible Door can be installed to open from the right or to the left to meet the requirements of your laundry room.

Wrinkle Release

Save ironing time! If your laundry won't be promptly removed from the dryer at the end of the cycle, use Wrinkle Release program to help reduce wrinkling by continuing to tumble clothing without heat.

Specifications:

Plug Type NONE

Container Loading 42/84/84 20'/40'/HC

IEC SYSTEM FOR CONFORMITY TESTING TO STANDARDS FOR SAFETY OF ELECTRICAL EQUIPMENT (IECEE)

Electrolux Major Appliances International 10200 David Taylor Drive Charlotte, NC 28262 USA www.philco-intl.com

Specifications sheet colors may vary depending on equipment.

Design and Specifications subject to change without notice. Images may vary from actual model.

MED10ZEMW 12/10/2015